

Endur-O-Seal USA Inc.

EOS OIL-X-OUT DEGREASER / OIL REMOVER

PRODUCT NAME: EOS OIL-X-OUT

METHOD OF APPLICATION

MANUFACTURER:

ENDUR-O-SEAL USA, Inc.
Pinehurst, Texas 77362
1-800-259-8855

PRODUCT DESCRIPTION:

OIL-X-OUT : Is a heavy-duty concrete cleaner concentrate that is a proprietary biodegradable formulation for removal of oil and grease stains from concrete drives, foundations and slabs.

OIL-X-OUT degreaser/ oil remover is a synergistic blends of detergents, chalets and degreasers that are environmentally safe.

OIL-X-OUT emulsifies and lifts contaminants from the pores within the concrete.

OIL-X-OUT can be used on new masonry as well as restoration /renovation applications. It is ideal for shop or factory floors, oil and bulk fuel storage and transfer facilities, heavy equipment manufacturing and repair facilities, parking deck lots and driveways. It is also applicable in restaurant kitchen, galleys (rated A4 by the USDA)

PRIMARY BENEFITS

- Non acidic
- Highly economical
- Non flammable/non combustible
- Does not contain MEK
- Does not etch concrete
- Water based
- No Nauseous odors

Apply by low-pressure spray (30-psi max), brush or mop. Apply OIL-X-OUT Granules liberally over OIL-X-OUT Liquid Degreaser / Cleaner and agitate vigorously with a stiff bristle brush. Allow the cleaner to react and emulsify the stain for surface containment's. Follow by rinsing thoroughly with clean fresh water utilizing a high-pressure system (500-psi min.) is recommended. Brush and reapply as necessary on heavily contaminated areas or deposits. Application rates will vary with given conditions.

APPLICATION RATES

Light Contamination:

150 Square feet per gallon

Moderate Contamination:

125 Square feet per gallon

Heavy Contamination:

75 Square feet per gallon

Extra Heavy Contamination:

Minimum 2 applications @
100 Sq. Ft. Per each gallon

PRECAUTIONS

Always use proper industrial hygiene Procedures. Refer in MSDS for further details.

Eye Protection: Cup type chemical goggles
Clothing: N/A. Avoid any contact with skin. Wear liquid proof neoprene gloves.

Ventilation: Avoid breathing vapors or mist. Use approved SCBA in confined areas.

Storage: Store in original containers. Do not contaminate with iron, heavy metals, copper alloys, caustic or paper products. Store containers in a cool area out of direct Sunlight.

AVAILABILITY AND SHIPPING INFORMATION

Available in five (5) gallon pails. Storage should be maintained between 32°F and 100°F and out of direct sunlight.

WARRANTY

The information and recommendations made herein are based on EOS research and that of others and are believed to be accurate. No Guarantee of test accuracy is made due to the considerable number of variables which can affect field application and performance of EOS products including but not limited to surface conditions, job conditions. Users and purchasers are encouraged to determine the suitability of this product for particular purposes. EOS SYSTEMS warrants this product to conform to stated specifications and be free of defects at time of shipment. The company makes no other warranties either express or implied.

CUSTOMER/TECHNICAL SERVICE

EOS SYSTEMS provides a variety of technical services regarding the function and use of EOS product. If you have any questions please contact your EOS sales representative for further information 1-281-259-8855.

SAFETY INFORMATION

Please refer to Material Safety Data Sheet