

# SAFETY DATA SHEET

DATE PREPARED: June 18, 2015

PAGE 1 OF 5

=====

ENDUROSEAL USA INC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your conditions would necessitate other appropriate methods.

## SECTION 1. PRODUCT IDENTIFICATION

### PRODUCT NAME:

SDS NUMBER 1

EOS POLY TOP SEALER CSx-20

Recommended use of the product and restrictions use identified uses: We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

### MANUFACTURER:

EOS Systems

Endur-O-Seal USA, Inc.

12502 LAZYWOOD LANE

PINEHURST, TEXAS 77362

TEL (800) 259-8855 EMAIL [ADMIN@ENDUROSEAL.COM](mailto:ADMIN@ENDUROSEAL.COM)

EMERGENCY TELEPHONE NUMBER 281 356 5117

CHEMICAL FAMILY: AQUEOUS POLYSILOXANE DISPERSION – TEFLON SEALER

THESE PRODUCTS ARE AQUEOUS BASED PENETRATING COMPOUNDS FOR WATERPROOFING OF NATURAL AND SYNTHETIC MATERIALS. REFER TO PRODUCT BULLETINS FOR SPECIFIC APPLICATION DATA.

## SECTION 2. HAZARDS IDENTIFICATION

### POTENTIAL HEALTH EFFECTS:

#### INGESTION:

IRRITATION OF MUCOUS MEMBRANES OF THROAT, ESOPHAGUS AND STOMACH WHICH MAY RESULT IN VOMITTING.

#### SKIN CONTACT:

NOT SIGNIFICANT: MAY CAUSE MILD SKIN IRRITATION. SKIN CHAPPING MAY DEVELOP AFTER EXTREME REPEATED CONTACT, PROGRESSING TO DERMATITIS IF HANDS ARE NOT WASHED.

#### INHALATION:

MILD IRRITATION OF THE UPPER RESPIRATORY TRACT POSSIBLE FOLLOWED BY DIZZINESS, HEADACHE.

#### EYE CONTACT:

MAY CAUSE A MILD BURNING SENSATION/ IRRITATION.

MEDICAL CONDITIONS AGGRAVATED AS STATED ABOVE.

#### CHRONIC EFFECTS / CARCINOGENICITY:

THIS PRODUCT OR ONE OF ITS INGREDIENTS PRESENT 0.1% OR MORE IS NOT LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN BY OSHA, IARC, NTP OR ACGIH.

#### MEDICAL LIMITATIONS:

RESTRICT CONTACT BY PERSONS WITH ACNE, SKIN SENSITIVITY OR SKIN DISEASE, AS EXTENDED EXPOSURE COULD AGGRAVATE THESE CONDITIONS.

#### EFFECTS OF OVEREXPOSURE:

ACUTE: CENTRAL NERVOUS SYSTEM DEPRESSION WITH EXTREME EXPOSURE; EFFECTS MAY INCLUDE ANESTHESIA, COMA, RESPIRATORY ARREST. OXYGEN DEPRIVATION IS POSSIBLE IF WORKING IN A CONFINED NON VENTILATED AREA.

CHRONIC: NO KNOWN MAJOR CUMMULATIVE OR LATENT EFFECTS HAVE BEEN REPORTED.

## SECTION 2. INGREDIENTS/ COMPOSITION

PRODUCTS/

CAS NUMBER(S)

ACGIH TLV OSHA PEL  
TWA STEL TWA STEL UNITS

APPROX.  
WGHT.%

CONTAINS ONE OR MORE OF THE FOLLOWING  
SILANES/SILOXANES:  
AMINOETHYLAMINOPROPYLPOLYSILOXANES  
SAFETY DATA SHEET  
DATE PREPARED: June 18, 2015

2-7.4 MIXTURE

PAGE 2 OF 5

### INGREDIENTS/ COMPOSITION CONTINUED

67923-07-3	NF	NE	NE	NF	NA	
DIMETHYL, HEXYSILOXANES						
157709-77-8	NA	NE	NA	NE	NA	
SILANOL/STPD						
68554-67-6	NF	NE	NF	NE	NA	
EXPANSION AGENTS (MIXTURE)						
68155-38-4	NE	NE	NE	NE	NA	< 2
112-90-3						
ALCOHOLS						MIXTURE
64-17-5						< 5
123-17-1						
CROSSLINKING AGENT						
29812-79-1	NE	NE	NE	NE	NA	< 1
DEIONIZED WATER	NE	NE	NE	NE	NA	78.6 – 87
NONHAZARDOUS MATERIALS	NE	NE	NE	NE	NA	7.5 -10

### SECTION 4. FIRST AID MEASURES

#### INGESTION:

DO NOT INDUCE VOMITING. IF VOMITING OCCURS KEEP AIRWAY CLEAR. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL ATTENTION IMMEDIATELY.

#### SKIN CONTACT:

WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES AND FOOTWEAR. SEEK MEDICAL ATTENTION IF SYMPTOMS ARISE.

#### INHALATION:

REMOVE TO FRESH AIR, RESTORE BREATHING IF NEEDED; ADMINISTER OXYGEN; SEEK MEDICAL HELP IF REQUIRED.

#### EYE CONTACT:

FLUSH EYES THOROUGHLY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION.

#### NOTES TO PHYSICIAN:

GASTRIC LAVAL ONLY IF A LARGE QUANTITY HAS BEEN INGESTED. TREAT SYMPTOMATICALLY.

### SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT: (AQUEOUS SOLUTION) >93.5 °C (MIN) >200 °F (MIN)

METHOD: TCC

AUTOIGNITION TEMP: >482 °C >900 °F

#### FLAMMABLE LIMITS IN AIR:

% BY VOLUME UPPER N/A

% BY VOLUME LOWER N/A

SENSITIVITY TO MECHANICAL IMPACT: NO

SENSITIVITY TO STATIC DISCHARGE: NONE EXPECTED; MATERIAL HAS A FLASHPOINT ABOVE 200 °F.

#### EXTINGUISHING MEDIA:

FOAM, DRY CHEMICAL, CARBON DIOXIDE. WATER MAY BE INEFFECTIVE UNLESS USED IN FAVORABLE CONDITIONS BY TRAINED FIREFIGHTERS.

#### SPECIAL FIREFIGHTING PROCEDURES:

MINIMIZE BREATHING OF GASES, VAPOR FUMES OR DECOMPOSITION PRODUCTS. USE (SCBA) IN ENCLOSED OR CONFINED AREAS. WATER CAN BE USED TO COOL AND PROTECT MATERIALS AND MEN, DISPERSE VAPORS, FLUSH SPILLS AWAY FROM EXPOSURES.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

CONFINE AREA TO CLEAN-UP PERSONNEL. VENTILATE AREA AND WEAR PROTECTIVE GEAR AS REQUIRED, WIPE UP SPILL WITH AN INERT MATERIAL AND PLACE IN AN APPROVED CONTAINER FOR DISPOSAL. REMOVE SOURCES OF IGNITION. DISPOSE OF EXPENDED MATERIAL AND ABSORBENTS WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

SAFETY DATA SHEET

DATE PREPARED: June 18, 2015

PAGE 3 OF 5

## SECTION 7. HANDLING AND STORAGE

- DO NOT MIX WITH INCOMPATIBLE MATERIALS.
- USE A PROPER GROUP STRAP ON HANDLING AND PUMPING EQUIPMENT.
- PREFERABLY UTILIZE EXPLOSION PROOF ELECTRICAL EQUIPMENT.
- RECOMMENDED STORAGE SHOULD BE ABOVE 0 °C (32 °F) AND BELOW 38 °C (100 °F.)
- KEEP ORIGINAL OR STORAGE CONTAINERS CLOSED WHEN NOT IN USE.
- AVOID BREATHING VAPORS.
- AVOID CONTACT WITH SKIN AND EYES.
- USE ONLY IN WELL VENTILATED AREAS.
- SHELF LIFE: USE WITHIN 6 MONTHS

## SECTION 8. PERSONAL PROTECTION/ EXPOSURE LIMITS

RESPIRATORY PROTECTION: USE IN WELL VENTILATED AREA. USE APPROVED NIOSH RESPIRATOR IF TLV IS EXCEEDED.

PROTECTIVE GLOVES: RUBBER

EYE AND FACE PROTECTION: SAFETY GLASSES

ENGINEERING: EXHAUST VENTILATION, SHOWERS, EYE WASH STATIONS

SKIN AND BODY CONTACT: IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE SKIN CONTACT. WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES.

HYGIENE MEASURES: ALWAYS OBSERVE GOOD PERSONAL HYGIENE MEASURES, SUCH AS WASHING AFTER HANDLING THE MATERIAL AND BEFORE EATING, DRINKING, AND/OR SMOKING. ROUTINELY WASH WORK CLOTHING AND PROTECTIVE EQUIPMENT TO REMOVE CONTAMINENTS.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INITIAL BURNING POINT:	100 °C	212 °F
VAPOR PRESSURE (20 °C)	< 5	
VAPOR DENSITY: (AIR=1)	UNKNOWN	
MELTING POINT:	UNKNOWN	
FREEZING POINT:	0 °C	32 °F
APPEARANCE:	GREY / WHITE HAZY LIQUID	
ODOR:	SLIGHT AMINE / LEMON ODOR	
EVAPORATION RATE (BuAc =1)	< 1	
% VOLATILE BY VOLUME:	1-5%	
V.O.C. CONTENT:	< 0.165 Lb/ Gal	
SPECIFIC GRAVITY (WATER = 1)	1.03 – 1.10	
SOLUBILITY IN H2O AT 20 °C	APPRECIABLE	

## SECTION 10. STABILITY AND REACTIVITY

STABILITY:	STABLE
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR
HAZARDOUS THERMAL DECOMPOSITION/ COMBUSTION PRODUCTS:	FUMES/ SMOKE/ CARBON MONOXIDE/ ALDEHYDES/ SILICON DIOXIDE/ FORMALDEHYDE/
INCOMPATIBILITY (MATERIALS TO AVOID):	STRONG OXIDANTS/ CONCENTRATED OXYGEN/ SODIUM HYPO CHLORITE/ CALCIUM HYPOCHLORITE.
CONDITONS TO AVOID:	KEEP AWAY FROM HEAT, SPARKS, AND L=FLAMES, AVOID ANY SOURCE OF IGNITION. AVOID CONTACT WITH ACIDIC, BASIC, OR OXIDIZING AGENTS AND METALLIC CATALSYTS LIKE TIN SOAPS AND NOBLE METALS

## SECTION 11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

**ACUTE ORAL TOXICITY:** LOW TOXICITY IF SWALLOWED. SMALL AMOUNTS SWALLOWED INCIDENTALLY AS A RESULT OF NORMAL HANDLING OPERATIONS ARE NOT LIKELY TO CAUSE INJURY; HOWEVER, SWALLOWING LARGER AMOUNTS MAY CAUSE INSUJURY  
**INHALATION:** NO DATA AVAILABLE

SAFETY DATA SHEET

DATE PREPARED: June 18, 2015

PAGE 4 OF 5

## TOXICOLOGICAL INFORMATION CONTINUED

**INGESTION:** NO DATA AVAILABLE  
**SKIN CORROSION/IRRITATIONS:** BRIEF CONTACT IS ESSENTIALLY NONIRRITATION TO SKIN. PROLONGED CONTACT MAY CAUSE MODERATE SKIN IRRITATION. REPEATED CONTACT MAY CAUSE MODERATE SKIN IRRITATION.  
**SERIOUS EYE DAMAGE/EYE IRRITATION:** MIST MAY CAUSE EYE IRRITATION  
**SENSITIZATION:** NO DATA AVAILABLE  
**CARCINOGENICITY:** NO DATA AVAILABLE  
**MUTAGENICITY:** NO DATA AVAILABLE  
**REPRODUCTIVE TOXCITY:** NO DATA AVAILABLE

## SECTION 12. ECOLOGICAL INFORMATION

Eco toxicological information on this product or is components appear in this section when such data is available.

**ECOTOXICITY:** NO DATA AVAILABLE  
**PERSISTENCE AND DEGRADABILIT:** THE PRODUCT IS NOT BIODEGRADABLE  
**BIOACCUMULATIVE POTENTIAL:** NO DATA AVAILABLE  
**MOBILITY:** NO DATA AVAILBLE

## SECTION 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** PRODUCT IS NON TOXIC AND NON HAZARDOUS. THIS CAN BE DISPOSED OF IN AN APPROPRIATE DIPOSAL MANNER IN ACCORDANCE WITH APPLICABLE LAWS AND REGULATIONS.

## SECTION 14. TRANSPORT INFORMATION

**DOT SHIPPING NAME:** AQUEOUS POLY SILOXANE DISPERSION – TEFLON SEALER  
**DOT HAZARD CLASS:** N/A  
**PLACARDS:** N/A  
**DOT I.D. NUMBER:** N/A  
**REPORTABLE QUANTITY:** N/A  
**RESTRICIONS:** N/A

## SECTION 15. REGULATORY INFORMATION

**TSCA:** THIS MATERIAL OR ITS COMPONENTS ARE LISTED ON THE TSCA INVENTORY LIST AND COMPLY WITH APPLICABLE RULES AS OF THIS WRITING.

**SARA 302:** NONE FOUND


**SARA 311 & 312:** NONE FOUND

**SARE 312:** THIS MATERIAL DOES NOT CONTAIN ANY INGREDIENTS ON THE LIST OF TOXOC CHEMICALS SUBJECT TO SECTION 313 OF THE SUPERFUND AMENDEMENTS AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III), IN EXCESS OF THE APPLICABLE MINIMUM CONCENTRATUONS AS PER SECTION 372.38 (a).

## SECTION 16. ADDITIONAL INFORMATION

**HAZARD RATING SYSTEM:**

MFPA No. 704, 1985 EDITION



=====

**ADDITIONAL INFORMATION CONTINUED**

**HMIS**

<b>HEALTH</b>	0
<b>FLAMMABILITY</b>	0
<b>REACTIVITY</b>	0
<b>PERSONAL PROTECTION</b>	0

- 4. Severe Hazard**
- 3. Serious Hazard**
- 2. Moderate Hazard**
- 1. Slight Hazard**
- 0. Minimal Hazard**

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH CFR 1910. 1200. ALL INFORMATION, RECOMMENDATIONS AND SUGGESTIONS APPEARING HEREIN CONCERNING OUR PRODUCT(S) ARE BASED UPON TESTS AND DATA BELIEVED TO BE RELIABLE, HOWEVER, IT IS THE USER'S SOLE RESPONSIBILITY TO DETERMINE THE SAFETY, TOXICITY AND SUITABILITY FOR HIS OWN USE OF THE PRODUCTS DESCRIBED HEREIN. SINCE THE ACTUAL USE OF THESE PRODUCTS IS BY OTHERS AND BEYOND OUR CONTROL, NO GUARENTEE EXPRESSED OR IMPLIED IS MADE BY ENDUR-O-SEAL USA, Inc. AS TO THE EFFECTS OF SUCH USE, INCLUDING THE RESULTS TO BE OBTAINED OR THE SAFETY AND TOXICITY OF THE PRODUCTS NOR DOES ENDUR-O-SEAL ASSUME ANY LIABILITY ARISING OUT OF THE USE BY OTHERS OF THE PRODUCTS REFERRED TO HEREIN. NOR IS THE INFORMATION HEREIN TO BE CONSTRUED AS ABSOLUTELY COMPLETE SINCE ADDITIONAL INFORMATION MAY BE NECESSARY OR DESIRABLE WHEN PARTICULAR OR EXCEPTIONAL CONDITIONS OR CIRCUMSTANCES EXIST OR BECAUSE OF APPLICABLE LAWS OR GOVERNMENT REGULATION.

NA = NOT APPLICABLE  
NE = NOT ESTABLISHABLE  
NF = NONE FOUND