

Endur-O-Seal USA Inc.

EOS CSx20 STAIN

OIL, GREASE & SOLVENT RESISTANT PENETRATING SEALER FOR CONCRETE /WITH COLOR FOR POSITIVE SIDE SURFACE

PRODUCT NAME: EOS CSx20 STAIN

MANUFACTURER:

ENDUR-O-SEAL USA, Inc.
Pinehurst, Texas 77362
1-800-259-8855

PRODUCT DESCRIPTION:

EOS CSx-2O Stain is a unique waterborne, non-flammable polysiloxane/ Teflon penetrating sealer/stain. It is specifically engineered for the treatment of concrete parking decks or maintenance areas. EOS CSx-2O Stain is a highly cost effective option to urethane or epoxy deck coatings. EOS CSx-2O Stain comes in ADA Brick Red, White, Black, 419 Charcoal and 418 Medium Gray. It is a penetrating system that is not susceptible to U.V. degradation

TECHNOLOGY:

The CSx-2O Stain system utilizes unique a chemistry of polysiloxanes coupled with proprietary technologies to provide high performance products that are environmentally safe. EOS CSx-2O Stain is a highly reactive, cross-linked polysiloxane, Teflon formulation that is capable of penetration rates 1/4"- 3/4" into the concrete. Broom finished surfaces may attain 1 1/2 inches. The formula attaches itself to the substrate particles by electrochemical means. During the curing process the system reacts with certain elements in the concrete to form a sub-surface vapor permeable elastomeric membrane. The membrane allows the treated matter to breathe normally while impeding contaminants from spreading,

wetting and ground moisture absorption through capillary channeling. EOS CSx-2O Stain may increase the slip coefficient when applied on smooth steel trowel finished surfaces.

PRIMARY BENEFITS

- Long – term performance
- Vapor permeable
- U.V. (Ultraviolet) resistant / extends product life.
- Oil, Grease and Solvent resistant.
- Very cost effective versus urethanes and epoxies.
- Prevents the water absorption/retention required for the growth of fungi or algae.
- Prevents adhesion of dirt and organic pollutants.
- Very low VOC's / non-toxic / non-hazardous.
- Provides protection in extreme temperatures (between -50°F and + 225°F)

TECHNICAL DATA

V.O.C. Content:	<0.27 lbs. /Gal
Flashpoint:	>+212°F
Penetration:	0.18 – 0.44 in
U.V. Resistance (QUV 7500 Hrs)	Pass
Breathability ASTM D1653	96.6%
Water Leakage ASTM E 514	99.4%
NCHRP 244 Chloride Absorption	98.3%
Simulated Wind Driven Rain (FS TTP 0035)	Pass

SURFACE PREPARATION

The material to be treated should be dry and free of non-integral dust, dirt, mildew, algae or alkali salts. If being applied to an existing structure, the substrate should be thoroughly washed to remove all efflorescence, dirt, mildew and fungi. Allow adequate time for drying prior to application. A broom or shot blast surface is recommended. *Surface can become slick without proper surface preparation.*

METHOD OF APPLICATION

EOS CSx-2O Stain can be applied by means of spraying with a conventional, airless (60 psi or below), or Hudson pump up type sprayer. **Roller application is preferred!** Make sure the masonry, brick and clay substrate to be treated is dry (15% moisture content maximum). Agitate the sealer as indicated on the label; utilize as is. DO NOT dilute or otherwise alter the material.

COVERAGE

COVERAGE FOR GENERAL CONDITIONS

Apply in accordance with the rates stated below or per architectural guide specifications. The following are approximate and may vary due to porosity of material to be treated.

- Poured in place concrete: 100 – 200 square feet per gallon (dependent on concrete condition)
- Pressed concrete pavers: 100 – 200 square feet per gallon (dependent on concrete porosity)

SEE GUIDE SPECIFICATIONS FOR DETAILS

PACKING AND STORAGE

Available in five (5) gallon pails. Storage should be maintained in sealed containers between 40° F and 100° F and **out of direct sunlight.** Product is specially mixed to order with low shelf-life expectancy and should be used within 6-12 months post order.

WARRANTY

The information and recommendations made herein are based on EOS research and that of others and are believed to be accurate. No Guarantee of test accuracy is made due to the considerable number of variables which can affect field application and performance of EOS products including but not limited to surface conditions, job conditions. Users and purchasers are encouraged to determine the suitability of this product for particular purposes. EOS SYSTEMS warrants this product to conform to stated specifications and be free of defects at time of shipment. The company makes no other warranties either express or implied.

CUSTOMER/TECHNICAL SERVICE

EOS SYSTEMS provides a variety of technical services regarding the function and use of EOS product. If you have any questions please contact your EOS sales representative for further information 1-281-259-8855.

SAFETY INFORMATION

Please refer to Material Safety Data Sheet