

Safety Data Sheet

ENDUR-O-SEAL USA INC

Product Name: EUREPOXY – PART B

Issue Date: 05/31/2015

User must read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. Product and Company Identification

Product Name

EUREPOXY PART B

COMPANY IDENTIFICATION

Endur-O-Seal USA Inc
12502 Lazywood St
Pinehurst, TX 77362

Customer Information Number: 800-259-8855\

2. Hazards Identification

Emergency Overview - WARNING!

Color: AMBER

Physical State: Liquid.

Odor: Ammonical

Hazards of product:

WARNING! May cause allergic skin reaction. May cause eye irritation. May cause skin irritation. Isolate area.

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Health Effects

Eye Contact: May cause eye damage. Corneal injury is possible.

Skin Contact: Prolonged contact may cause skin burns with local redness. Repeated contact may cause skin irritation with local redness.

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Skin Sensitization: Skin contact may cause an allergic skin reaction.

Inhalation: Excessive exposure may cause irritation to upper respiratory tract (nose and throat).

Ingestion: Very low toxicity if swallowed.

Aspiration hazard: Based on physical properties, not likely to be an aspiration hazard.

Cancer Information: Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol A (DGEBA). Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic.

3. Composition Information

Component	CAS #	Amount
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	5-7.0 %
DIMER FATTY ACID_POLYETHYLENEPOLYAMINE ADDUCT	68410-23-1	65.0 %
Benzyl Alcohol	100-51-6	25-30 %

4. First-aid measures

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin Contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye Contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: Wash out mouth with water. Seek medical attention immediately. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), no additional symptoms and effects are anticipated.

Indication of immediate medical attention and special treatment needed

No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire Fighting Measures

Suitable extinguishing media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective. Water fog, applied gently may be used as a blanket for fire extinguishment.

Extinguishing Media to Avoid: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is emitted when burned without sufficient oxygen.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Water fog, applied gently may be used as a blanket for fire extinguishment. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Sand. Polypropylene fiber products. Polyethylene fiber products. Remove residual with soap and hot water. Collect in suitable and properly labeled containers. Residual can be removed with solvent. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed. Consult appropriate solvent Safety Data Sheet for handling information and exposure guidelines. See Section 13, Disposal Considerations, for additional information.

7. Handling and Storage

Handling

General Handling: Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Storage

Store in a cool, dry place.

In original unopened containers

Shelf life: Use within	Storage temperature:
24 Months	5 - 43 °C
	40 - 110 °F

8. Exposure Controls / Personal Protection
--

Exposure Limits

None established

Personal**Protection****Eye/Face Protection:** Use safety glasses (with side shields).**Skin Protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Neoprene. Polyvinyl chloride ("PVC" or "vinyl").

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.**Engineering Controls****Ventilation:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

9. Physical and Chemical Properties

Appearance**Physical State**

Liquid.

Color

Pigmented or Clear

Odor

Ammoniacal

Odor Threshold

No test data available

pH

Not applicable

Melting Point

Not applicable

Freezing Point

Not determined

Boiling Point (760 mmHg) ≥ 300 °F (≥ 300 °F) *Literature* .**Flash Point - Closed Cup**176.7 - 190.6 °C (350.1 - 375.1 °F) *PMCC, ASTM D93***Evaporation Rate (Butyl Acetate = 1)**

No test data available

Flammability (solid, gas)

No

Flammable Limits In Air**Lower:** Not applicable**Upper:** Not applicable**Vapor Pressure**

Not applicable

Vapor Density (air = 1)	Not applicable
Specific Gravity (H₂O = 1)	1.11 - 1.14
Solubility in water (by weight)	Insoluble
Partition coefficient, n-octanol/water (log Pow)	No data available for this product. See Section 12 for individual component data. Not determined
Autoignition Temperature	No test data available
Decomposition Temperature	No test data available
Dynamic Viscosity	2700 - 6000 cPs @ 25 °C ASTM D445
Kinematic Viscosity	No test data available
Explosive properties	no data available
Oxidizing properties	no data available
Molecular Weight	Not determined

10. Stability and Reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions

Polymerization will not occur by itself. Masses of more than one pound (0.5 kg) of product plus an epoxide will cause irreversible polymerization with considerable heat build-up.

Conditions to Avoid: Avoid short term exposures to temperatures above 300 °C (572 °F). Avoid prolonged exposure to temperatures above 250 °C (482 °F). Potentially violent decomposition can occur above 350 °C (662 °F). Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid.

Incompatible Materials: Avoid contact with oxidizing materials. Avoid contact with: Acids. Bases. Avoid unintended contact with epoxides.

Hazardous decomposition products

Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition.

11. Toxicological Information

Acute Toxicity

Ingestion

As product: Single dose oral LD50 has not been determined. Based on information for component(s): LD50, rat > 5,000 mg/kg

Dermal

As product: The dermal LD50 has not been determined. For the major component(s): LD50, rabbit > 20,000 mg/kg

Inhalation

The LC50 has not been determined.

Eye damage/eye irritation

May cause eye damage or irritation.

Skin corrosion/irritation

Prolonged contact may cause skin burns and irritation with local redness. Repeated contact may cause skin burns.

Sensitization**Skin**

Skin contact may cause an allergic skin reaction. A component in this mixture has caused allergic skin reactions in humans.

Respiratory

No relevant data found.

Repeated Dose Toxicity

No relevant data found.

Chronic Toxicity and Carcinogenicity

Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol A (DGEBA). Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic.

Developmental Toxicity

Resins based on the diglycidyl ether of bisphenol A (DGEBA) did not cause birth defects or other adverse effects on the fetus when pregnant rabbits were exposed by skin contact, the most likely route of exposure, or when pregnant rats or rabbits were exposed orally.

Reproductive Toxicity

In animal studies, did not interfere with reproduction.

Genetic Toxicology

Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others. Contains component(s) which were negative in animal genetic toxicity studies.

12. Ecological Information

ToxicityData for Component: **Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 h: 2 mg/l

Aquatic Invertebrate Acute Toxicity

EC50, Daphnia magna (Water flea), static test, 48 h, immobilization: 1.8 mg/l

Aquatic Plant Toxicity

ErC50, Scenedesmus capricornutum (fresh water algae), static test, Growth rate inhibition, 72 h: 11 mg/l

Toxicity to Micro-organisms

IC50; Bacteria, 18 h: > 42.6 mg/l

Aquatic Invertebrates Chronic Toxicity Value

Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, NOEC: 0.3 mg/l

Data for Component: **Benzyl Alcohol**

Not expected to be acutely toxic, can cause adverse effects if ingested by waterfowl or aquatic life.

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 h: >460mg/L

C50, Lepomis macrochirus (Bluegill sunfish), static test, 96 h: 600 mg/l

Aquatic Plant Toxicity

EbC50, Pseudokirchneriella subcapitata (green algae), Growth inhibition (cell density reduction), 72 h: 770 mg/l

NOEC, Pseudokirchneriella subcapitata (green algae), Growth inhibition (cell density reduction), 72 h: 310 mg/l

Persistence and Degradability

Data for Component: Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

OECD Biodegradation Tests:

Biodegradation	Exposure Time	Method	10 Day Window
12 %	28 d	OECD 302B Test	Not applicable

Indirect Photodegradation with OH Radicals

Rate Constant	Atmospheric Half-life	Method
6.69E-11 cm ³ /s	1.92 h	Estimated.

Theoretical Oxygen Demand: 2.35 mg/mg

Data for Component: Dimer Fatty Acid Polyethylenepolyamine Adduct

No Data available

--

Chemical Oxygen Demand: 2.09 mg/mg

Bioaccumulative potential

Data for Component: Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient, n-octanol/water (log Pow): 3.242 Estimated.

Mobility in soil

Data for Component: Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

Mobility in soil: Potential for mobility in soil is low (Koc between 500 and 2000)., Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient, soil organic carbon/water (Koc): 1,800 - 4,400 Estimated.

Henry's Law Constant (H): 4.93E-05 Pa*m³/mole.; 25 °C

Data for Component: Benzyl Alcohol

Mobility in soil: Expected to be relatively immobile in soil (Koc > 5000).

13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. Transport Information

DOT Non-Bulk
NOT REGULATED

DOT Bulk/IMDG

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: Dimer Fatty acid (C18) Polyamidoamine Resin

Hazard Class: 9 **ID Number:** UN3082 **Packing Group:** PG III

EMS Number: F-A,S-F

Marine pollutant.: Yes

ICAO/IATA

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: Dimer Fatty Acid (C18) Polyamidoamine Resin

Hazard Class: 9 **ID Number:** UN3082 **Packing Group:** PG III

Cargo Packing Instruction: 964

Passenger Packing Instruction: 964

Additional Information

MARINE POLLUTANT

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Regulatory Information

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes
Delayed (Chronic) Health Hazard	No
Fire Hazard	No
Reactive Hazard	No
Sudden Release of Pressure Hazard	No

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act):
Pennsylvania Special Hazardous Substances List: To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)
 This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

US. Toxic Substances Control Act
 All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

16. Other Information

Label Requirements: CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL IF SWALLOWED. MAY CAUSE TARGET ORGAN DAMAGE BASED ON ANIMAL DATA.

HMIS RATINGS **HEALTH – 2**
 FIRE – 1
 PHYSICAL HAZARD – 0
 PERSONAL PROTECTION

Recommended Uses and Restrictions

Identified uses

Used in applications such as: Adhesives. Casting. Tooling. Civil engineering. Composites. Marine and protective coatings. Potting and encapsulation.

Revision

Identification Number: 201401 / 0001 / Issue Date 01/31/2014 / Version: 1.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

The CONSTRUCTION RESINS CORP urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped.

Issue Date: 05/31/2015

conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.