

PRODUCT BULLETIN

EOS DEEP PENETRATING SEALERS

**DENSIFY AND SEAL CONCRETE SLABS AND WALLS, CONCRETE
BLOCKS. STOPS MOISTURE MIGRATION OR MAJOR SEEPAGE**

**PRODUCT: EOS HYDRO BLOK PRIMARY BENEFITS
EOS CURE & SEAL**

MANUFACTURER / SUPPLIER

Endur-O-Seal USA, Inc.
12502 LAZYWOOD
PINEHURST, TEXAS 77362
1-800-259-8855

PRODUCT DESCRIPTION:

EOS HYDRO BLOK SEALER IS A WATERBORNE, NON-FLAMMABLE SILICATE PENETRATING SOLUTION IT IS SPECIFICALLY DESIGNED AS A CONCRETE SEALER/DENSIFIER FOR STOPPING MOISTURE MIGRATION OR MAJOR SEEPAGE OF BLOCKS, CONCRETE DECKS SLABS, WALLS, DRIVEWAYS, FOUNDATIONS OR OLD POROUS CONCRETE.

TECHNOLOGY;

EOS HYDRO BLOK, A PROPRIETARY AQUEOUS SOLUTION WITH SPECIAL PENETRATING AGENTS THAT HELP DEEP SEALING OF CONCRETE THAT HAS SEVERE MOISTURE PROBLEMS, SLUFFING OR DUSTING (CHALKING)

APPLICATION:

APPLY ONE (1) WET FILM OF EOS HYDRO BLOK TO DAMP CONCRETE APPLY AT A RATE OF 200 TO 400 400 SQ. FT. PER GAL. (APPROX.) PER SINGLE APPLICATION X 3 APPS. CAUTION SHOULD BE TAKEN TO AVOID PUDDLING IN LOW SPOTS. READ APPLICATION INSTRUCTIONS BEFORE USING. APPLICATOR MUST DETERMINE IF HIS/HER PROJECT IS SUITED FOR THIS PRODUCT

COVERAGE:

UP TO 400 SQ. FT. PER GALLON MAX.

RAPID PERFORMANCE
PRECIPITATES CALCIUM IONS
VAPOR PERMEABLE
REDUCES FREEZE/THAW SPALL
UV RESISTANT
STOPS SEEPAGE
STOPS MOISTURE MIGRATION

HARDENS AND INCREASES STRENGTH

INCREASES DENSITY
STOPS HAZARDOUS GASES

TECHNICAL DATA

VOC COMPLIANT

BOILING POINT 214 ° F

NO ODOR

pH: 7.9 CURED

FLASH POINT -0-

PENETRATION: (variable with density)

FREEZING POINT AS LIQUID: 32° .

AGITATE PRODUCT BEFORE USE

APPLICATION: HUDSON OR AIRLESS

WARRANTY: FREE OF DEFECTS AT TIME OF SHIPMENT. NO OTHER WARRANTIES EXPRESSED OR IMPLIED

**ENDUR-O-SEAL USA, INC.
EOS SYSTEMS**